



## Pyramid Sign Base Installation Instructions

- 1.** For Sign Bases with wheels: Use a Phillips screwdriver or power drill to install the wheels to the side of the sign base.
- 2.** Once the wheels are in place, insert the pole, making sure that it's in line with the base interior nub.
- 3.** Using two, 3/16" Allen Wrenches (not included), insert screw in designated hole at the top of the base.
- 4.** Move to designated location **before** filling.
- 5.** Remove cap on top of Sign Bases and fill with chosen filler:
  - 5a.** Water: 16 gallons (in freezing temps) or 19 gallons otherwise
  - 5b.** Base Gel & Water Mixture: 16 gallons (in freezing temps) or 19 gallons of water otherwise. Used to prevent evaporation or leakage if tipped over. Ignore install instructions on base gel package, follow our filling limits in freeze areas.
  - 5c.** Concrete
  - 5d.** Sand
- 6.** Once filled, replace cap on top of the sign base.

**Visit the Ideal Shield  
Youtube Channel for  
video installation**

Ph: (866) 825-8659  
Fax: (313) 842-7860  
[www.idealshield.com](http://www.idealshield.com)  
Email: [info@idealshield.com](mailto:info@idealshield.com)  
2525 Clark St - Detroit, MI 48209