


**TRAFFIC IMPACT BOLLARD (MODEL TIB-67-SA)
SINGLE STAND ALONE, UNRESTRICTED SPACING, SET AND POUR FEATURE**

ENGINEERED & DESIGNED FOR C40, P1 (CRASH TESTED PROTOCOL) PROPERLY INSTALLED, STOPPED 2430 lbs PASSENGER CAR AT 40MPH OR STOREFRONT EQUIVALENT ASTM F2656

PREFABRICATED BOLLARD MATERIALS PROVIDED



(QTY 1) EACH:
BOLLARD TUBE



(QTY 2) EACH:
PRE-CUT VERTICAL REBAR
(INSIDE BOLLARD)



(QTY 1) EACH:
BOLLARD COVER
STYLE PER CUSTOMER

MATERIALS PROVIDED BY INSTALLER

1. CONCRETE, 1.5 CUBIC YARDS PER BOLLARD
2. CHAIRS TO ELEVATE BOLLARDS ABOVE SUBGRADE

Jointly Developed



THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE PROPRIETARY AND CONFIDENTIAL AND FOR USE BY ONLY PERSONS WORKING ON PROJECT WITH BARRIER1 SYSTEMS INC. X IDEAL SHIELD. DO NOT COPY OR REPRODUCE. ALL RIGHTS RESERVED.

MATERIALS PROVIDED

DRAWINGS

SHEET: 5 OF 5

20190603-01-PD

SCALE: N.T.S.