



# PYRAMID SIGN BASE INSTALLATION INSTRUCTIONS

**Tools Needed: Two 3/16" Allen Wrench**

**Step #1:** For Sign Bases with wheels: Use a Phillips screwdriver or power drill to install the wheels to the side of the sign base.

**Step #2:** Once the wheels are in place, insert the pole, making sure it is set on the interior nub. If post hole does not line up exactly with sign base hole, lift post 1/4" to line up holes before inserting screw.

**Step #3:** Using two, 3/16" Allen Wrenches (not included), insert screw in designated hole at the top of the base.

**Step #4:** Move to designated location **before** filling.

**Step #5:** Remove cap from top of Sign Base and fill with chosen filler based on your stability needs.  
**\*Sign size and filler option affects tip point.**

**5a:** Water: 16 gallons in areas where temperatures freeze, otherwise fill to the top (19 gallons)

**5b:** Base Gel & Water Mixture: 16 gallons (in freezing temps) or 19 gallons of water otherwise. Used to prevent evaporation or leakage if tipped over. Ignore install instructions on base gel package, follow our filling limits in freeze areas.

**5c.** Pea Gravel: make sure signpost is installed before filling, use large funnel for easier install.

**5d.** Sand: make sure signpost is installed before filling, use large funnel for easier install.

**5e.** Concrete: make sure signpost is installed before filling, use large funnel for easier install.



**Visit the Ideal Shield Youtube  
Channel for video installation**

**Ph: (866) 825-8659  
Fax: (313) 842-7860  
www.idealshield.com  
Email: info@idealshield.com  
2525 Clark St - Detroit, MI 48209**