



# IDEAL SHIELD CLEARANCE ARM SYSTEM



## Clearance Bar Materials:

- Lo-Density Thermoplastic Polyethylene (LDPE)
- With Ultra-Violet and anti-static additives
- .250 Nominal Wall Thickness

## Clearance Bar Sizes:

- Length: 78"
- 5.25" Outside Diameter
- Lettering: Optional

## Clearance Bar Installation:

- Simple installation: eye bolts included with order
- Chains not included

## Clearance Arm Materials:

- 1 1/2 schedule 40 steel, sleeved in HDPE plastic
- HDPE plastic standard colors: yellow, red, black, blue, and other colors available
- Standard Height: 10 ft. (13 Ft Max)
- Standard Cross Bar Length: 10 Ft (10 Ft Max)
- Fittings: Alloy Magnesium, will not rust
- Optional: Swing collar mechanism to return Clearance Arm back to home position when hit

## Steel Bollard Size Options- Includes Sleeve Cover:

- 4" schedule 40 steel with plastic sleeve cover
- 6" schedule 40 steel with plastic sleeve cover
- Sleeve Cover Standard Colors: yellow, black, red, blue, other colors available
- Standard Lengths: 36", 42", 48", 52" (custom lengths available)
- Installation Options: Plate Mount or Core-In
- Base Plate Dimensions: 10" x 10" x 5/8" - (4) 15/16" Anchor Bolt holes
- Optional: (4) 3/4" x 6 1/4" Anchor Bolts

**CONTACT US FOR A QUOTE TODAY**

**[313] 551-2275**